

View Online at <https://aerobasegroup.com/nsn/5340-00-721-4957>

Thread Class:

3a rod connection

Thread Direction:

Right-hand rod connection

Thread Length:

1.250 inches rod connection and 1.340 inches rod connection

Shank Length:

Between 1.250 inches and 1.340 inches

Hole Diameter:

Between 0.2495 inches and 0.2500 inches

Shank Diameter:

0.438 inches

Overall Height:

0.625 inches

Overall Width:

Between 0.715 inches and 0.760 inches

End Radius:

Between 0.350 inches and 0.410 inches

Fork Span Width:

Between 0.485 inches and 0.490 inches

Distance From Pivot Pinhole Center To Rod Connection End:

Between 2.590 inches and 2.650 inches

Fork Arm Thickness:

0.115 mils and 0.135 centimeters

Fork Depth:

Between 0.930 inches and 0.950 inches

Thread Size:

0.438 inches rod connection

Material:

Steel comp 4130 or steel comp e4340 or steel comp 4340

Material Specification:

Mil-s-6758, cond c4 military specification 1st material response or mil-s-5000, cond c4 military specification 2nd material response or mil-s-5000, cond c4 military specification 3rd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

299-099-031, cb2, bell helicopter co mfr ref single treatment response

Style Designator:

Clevis

Thread Series Designator:

Unf rod connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A264a0

Mil-std (military Standard):

Mil-s-6758 spec.