

View Online at <https://aerobasegroup.com/nsn/5340-00-721-4957>

**Thread Class:**

3a rod connection

**Thread Direction:**

Right-hand rod connection

**Thread Length:**

1.250 inches rod connection and 1.340 inches rod connection

**Shank Length:**

Between 1.250 inches and 1.340 inches

**Hole Diameter:**

Between 0.2495 inches and 0.2500 inches

**Shank Diameter:**

0.438 inches

**Overall Height:**

0.625 inches

**Overall Width:**

Between 0.715 inches and 0.760 inches

**End Radius:**

Between 0.350 inches and 0.410 inches

**Fork Span Width:**

Between 0.485 inches and 0.490 inches

**Distance From Pivot Pinhole Center To Rod Connection End:**

Between 2.590 inches and 2.650 inches

**Fork Arm Thickness:**

0.115 mils and 0.135 centimeters

**Fork Depth:**

Between 0.930 inches and 0.950 inches

**Thread Size:**

0.438 inches rod connection

**Material:**

Steel comp 4130 or steel comp e4340 or steel comp 4340

**Material Specification:**

Mil-s-6758, cond c4 military specification 1st material response or mil-s-5000, cond c4 military specification 2nd material response or mil-s-5000, cond c4 military specification 3rd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

299-099-031, cb2, bell helicopter co mfr ref single treatment response

**Style Designator:**

Clevis

**Thread Series Designator:**

Unf rod connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A264a0

**Mil-std (military Standard):**

Mil-s-6758 spec.