

View Online at <https://aerobasegroup.com/nsn/5340-00-721-5283>

Fabrication Method (non-core):

Stamped

First Leg Length:

Between 1.547 inches and 1.578 inches

Second Leg Length:

Between 0.672 inches and 0.703 inches

Reinforcement Method (non-core):

Gusset both sides

Second Leg Width:

Between 0.615 inches and 0.625 inches

First Leg Hole Diameter:

Between 0.189 inches and 0.199 inches

Second Leg Hole Diameter:

Between 0.199 inches and 0.209 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.305 inches and 0.315 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.305 inches and 0.315 inches

First Leg Thickness:

Between 0.059 inches and 0.069 inches

Second Leg Thickness:

Between 0.059 inches and 0.069 inches

First Leg Width:

Between 0.615 inches and 0.625 inches

First Leg Distance Between Hole Centers Along Length:

Between 0.495 inches and 0.505 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.305 inches and 0.315 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.305 inches and 0.315 inches

First Leg End Radius:

Between 0.375 inches and 0.385 inches

Second Leg End Radius:

Between 0.375 inches and 0.385 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

First Leg Angle:

90.0 degrees

Special Features:

Furnished with one nut, plain, blind rivet

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/5 federal specification single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0