

View Online at <https://aerobasegroup.com/nsn/5340-00-721-7629>

Fabrication Method (non-core):

Machined

Mounting Hole Type:

Plain

First Leg Length:

0.875 inches

Second Leg Length:

1.250 inches

Second Leg Width:

0.500 inches

First Leg Hole Diameter:

Between 0.217 inches and 0.224 inches

Second Leg Hole Diameter:

Between 0.279 inches and 0.286 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Thickness:

0.062 inches

Second Leg Thickness:

0.062 inches

First Leg Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg End Radius:

0.250 inches

Second Leg End Radius:

0.250 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 4130

Material Specification:

Ams 6350 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Angle

Fsc Application Data:

Engine turbo-prop, acft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0