

View Online at <https://aerobasegroup.com/nsn/5340-00-723-2859>

Mounting Hole Type:

Plain and threaded

First Leg Length:

0.650 inches

Second Leg Length:

0.770 inches

Second Leg Width:

2.452 inches

Second Leg Corner Radius:

0.320 inches

First Leg Hole Diameter:

Between 0.216 inches and 0.229 inches

Second Leg Hole Diameter:

0.308 inches

Second Leg Distance Between Hole Centers Along Width:

1.3120 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.320 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.320 inches

First Leg Thickness:

0.309 inches

Second Leg Thickness:

0.039 inches

First Leg Width:

2.132 inches

First Leg Corner Radius:

0.220 inches

First Leg Distance Between Hole Centers Along Width:

0.1924 inches

First Leg Distance From Edge To Hole Center Along Width:

0.320 inches

First Leg Distance From Edge To Hole Center Along Length:

0.220 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

One hole

Features Provided:

Nut

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Second leg incl nut plate ms21048-4 riveted over second hole w/an125422 two places; used on tf41 engine

Material:

Stainless steel

Material Specification:

Ams 5512 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0