NSN 5340-00-723-5099

Swivel Caster - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-723-5099

Contar To Contar Distance Patuson Polt Holos Along Width
Center To Center Distance Between Bolt Holes Along Width: 4.875 inches
Center To Center Distance Between Bolt Holes Along Length:
6.750 inches
Wheel Quantity:
1
Safe Operating Load Rating:
1000.0 pounds
Material And Location:
Rubber
Wheel Type:
Pneumatic tire
Wheel Diameter:
10.000 inches
Features Provided:
Brake lock
Plate Style:
Rectangular
Wheel Bearing Type:
Tapered roller
Swivel Bearing Type:
Roller
Swivel Bearing Arrangement:
One row
King Bolt Bearing Type:
Roller
Tread Width:
3.000 inches
Caster Plate Length:
8.500 inches
8.500 inches Caster Plate Width:
Caster Plate Width:
Caster Plate Width: 7.000 inches
Caster Plate Width: 7.000 inches Caster Plate Mounting Hole Diameter:
Caster Plate Width: 7.000 inches Caster Plate Mounting Hole Diameter: 0.625 inches
Caster Plate Width: 7.000 inches Caster Plate Mounting Hole Diameter: 0.625 inches Style Designator:
Caster Plate Width: 7.000 inches Caster Plate Mounting Hole Diameter: 0.625 inches Style Designator: Swivel nonoffset
Caster Plate Width: 7.000 inches Caster Plate Mounting Hole Diameter: 0.625 inches Style Designator: Swivel nonoffset Shelf Life:
Caster Plate Width: 7.000 inches Caster Plate Mounting Hole Diameter: 0.625 inches Style Designator: Swivel nonoffset Shelf Life: N/a

No

NSN 5340-00-723-5099

Swivel Caster - Page 2 of 2



Fiig:

A25600