

View Online at <https://aerobasegroup.com/nsn/5340-00-725-2995>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

Between 1.109 inches and 1.141 inches

**Second Leg Length:**

Between 0.484 inches and 0.516 inches

**Second Leg Width:**

Between 0.797 inches and 0.828 inches

**Second Leg Corner Radius:**

0.125 inches

**First Leg Hole Diameter:**

Between 0.192 inches and 0.203 inches

**Second Leg Hole Diameter:**

0.138 inches

**Second Leg Distance Between Hole Centers Along Width:**

Between 0.422 inches and 0.453 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.172 inches and 0.203 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.234 inches and 0.266 inches

**First Leg Thickness:**

Between 0.109 inches and 0.141 inches

**Second Leg Thickness:**

Between 0.109 inches and 0.141 inches

**First Leg Width:**

Between 0.797 inches and 0.828 inches

**First Leg Corner Radius:**

0.125 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.391 inches and 0.422 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.234 inches and 0.266 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Two holes

**First Leg Angle:**

90.0 degrees

**Special Features:**

Threaded holes in second leg

**Heat Treatment:**

T-4 solution heat treated

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.