

View Online at <https://aerobasegroup.com/nsn/5340-00-725-2995>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 1.109 inches and 1.141 inches

Second Leg Length:

Between 0.484 inches and 0.516 inches

Second Leg Width:

Between 0.797 inches and 0.828 inches

Second Leg Corner Radius:

0.125 inches

First Leg Hole Diameter:

Between 0.192 inches and 0.203 inches

Second Leg Hole Diameter:

0.138 inches

Second Leg Distance Between Hole Centers Along Width:

Between 0.422 inches and 0.453 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.172 inches and 0.203 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.234 inches and 0.266 inches

First Leg Thickness:

Between 0.109 inches and 0.141 inches

Second Leg Thickness:

Between 0.109 inches and 0.141 inches

First Leg Width:

Between 0.797 inches and 0.828 inches

First Leg Corner Radius:

0.125 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.391 inches and 0.422 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.234 inches and 0.266 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

First Leg Angle:

90.0 degrees

Special Features:

Threaded holes in second leg

Heat Treatment:

T-4 solution heat treated

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.