

View Online at <https://aerobasegroup.com/nsn/5340-00-734-7713>

Cross Sectional Shape:

Circular recess

Inside Diameter:

3.875 inches

Hole Diameter:

1.063 inches

Width:

6.375 inches

Flange Thickness:

0.500 inches

Edge Shape:

Four radii sides, four holes

Length:

5.563 inches

Body Radius:

2.750 inches

Distance Between Holes Along Length:

3.875 inches

Distance Between Holes Along Width:

3.875 inches

Distance From First Hole Centerline To End Along Length:

0.875 inches

Distance From First Hole Centerline To End Along Width:

0.875 inches

Ear Radius:

0.531 inches

First Recess Inside Height:

1.094 inches

Inside Corner Radius:

0.563 inches

Body Thickness:

0.188 inches

First Recess Diameter:

3.875 inches

Outside Corner Radius:

0.375 inches

Body Outside Radius:

0.375 inches

Securing Device Type:

Threaded fastener

Mounting Opening Shape Style:

Unthreaded hole

End Application:

Nw/s: truck, tractor, 5-ton (m818, m931); truck, cargo, dropside, 5-ton, 6x6 (m813a1, m-923, m-925); truck, dump, 5-ton, 6x6 (m929, m930); crane, truck mounted, hyl 25-ton cat (cce); truck, cargo, 5-ton, 6x6, xlwb w/e

Inside Angle:

65.0 degrees

Special Features:

One square cornered tab 1-1/4 in. By 3/4 in. Located 13/32 in. Below centerline and extending 27/32 in. Above centerline, 3/8 in. Radius at base of tab

Material:

Iron cast

Fsc Application Data:

Transmission, truck

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A531c0