

View Online at <https://aerobasegroup.com/nsn/5340-00-734-7713>

**Cross Sectional Shape:**

Circular recess

**Inside Diameter:**

3.875 inches

**Hole Diameter:**

1.063 inches

**Width:**

6.375 inches

**Flange Thickness:**

0.500 inches

**Edge Shape:**

Four radii sides, four holes

**Length:**

5.563 inches

**Body Radius:**

2.750 inches

**Distance Between Holes Along Length:**

3.875 inches

**Distance Between Holes Along Width:**

3.875 inches

**Distance From First Hole Centerline To End Along Length:**

0.875 inches

**Distance From First Hole Centerline To End Along Width:**

0.875 inches

**Ear Radius:**

0.531 inches

**First Recess Inside Height:**

1.094 inches

**Inside Corner Radius:**

0.563 inches

**Body Thickness:**

0.188 inches

**First Recess Diameter:**

3.875 inches

**Outside Corner Radius:**

0.375 inches

**Body Outside Radius:**

0.375 inches

**Securing Device Type:**

Threaded fastener

**Mounting Opening Shape Style:**

Unthreaded hole

**End Application:**

Nw/s: truck, tractor, 5-ton (m818, m931); truck, cargo, dropside, 5-ton, 6x6 (m813a1, m-923, m-925); truck, dump, 5-ton, 6x6 (m929, m930); crane, truck mounted, hyl 25-ton cat (cce); truck, cargo, 5-ton, 6x6, xlwb w/e

**Inside Angle:**

65.0 degrees

**Special Features:**

One square cornered tab 1-1/4 in. By 3/4 in. Located 13/32 in. Below centerline and extending 27/32 in. Above centerline, 3/8 in. Radius at base of tab

**Material:**

Iron cast

**Fsc Application Data:**

Transmission, truck

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A531c0