## NSN 5340-00-735-0240

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-735-0240

Threaded
First Leg Length:
4.530 inches
Second Leg Length:
4.530 inches
Reinforcement Method (non-core):
Gusset both legs
Second Leg Width:
1.620 inches
Second Leg Corner Radius:
0.220 inches
First Leg Hole Diameter:
0.190 inches
Second Leg Hole Diameter:
0.190 inches
Second Leg Distance Between Hole Centers Along Width:
0.870 inches
Second Leg Distance Between Hole Centers Along Length:
3.880 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.530 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.220 inches
First Leg Thickness:
That Leg Thickness.
0.090 inches
•
0.090 inches
0.090 inches Second Leg Thickness:
0.090 inches  Second Leg Thickness: 0.090 inches
0.090 inches  Second Leg Thickness: 0.090 inches  First Leg Width:
0.090 inches  Second Leg Thickness: 0.090 inches  First Leg Width: 1.620 inches
0.090 inches  Second Leg Thickness: 0.090 inches  First Leg Width: 1.620 inches  First Leg Corner Radius:
0.090 inches  Second Leg Thickness: 0.090 inches  First Leg Width: 1.620 inches  First Leg Corner Radius: 0.220 inches
0.090 inches  Second Leg Thickness: 0.090 inches  First Leg Width: 1.620 inches  First Leg Corner Radius: 0.220 inches  First Leg Distance Between Hole Centers Along Width:
0.090 inches  Second Leg Thickness: 0.090 inches  First Leg Width: 1.620 inches  First Leg Corner Radius: 0.220 inches  First Leg Distance Between Hole Centers Along Width: 0.870 inches
0.090 inches  Second Leg Thickness: 0.090 inches  First Leg Width: 1.620 inches  First Leg Corner Radius: 0.220 inches  First Leg Distance Between Hole Centers Along Width: 0.870 inches  First Leg Distance From Edge To Hole Center Along Width:
0.090 inches  Second Leg Thickness: 0.090 inches  First Leg Width: 1.620 inches  First Leg Corner Radius: 0.220 inches  First Leg Distance Between Hole Centers Along Width: 0.870 inches  First Leg Distance From Edge To Hole Center Along Width: 0.530 inches
0.090 inches  Second Leg Thickness: 0.090 inches  First Leg Width: 1.620 inches  First Leg Corner Radius: 0.220 inches  First Leg Distance Between Hole Centers Along Width: 0.870 inches  First Leg Distance From Edge To Hole Center Along Width: 0.530 inches  First Leg Distance From Edge To Hole Center Along Length:
0.090 inches  Second Leg Thickness: 0.090 inches  First Leg Width: 1.620 inches  First Leg Corner Radius: 0.220 inches  First Leg Distance Between Hole Centers Along Width: 0.870 inches  First Leg Distance From Edge To Hole Center Along Width: 0.530 inches  First Leg Distance From Edge To Hole Center Along Length: 0.220 inches
0.090 inches  Second Leg Thickness: 0.090 inches  First Leg Width: 1.620 inches  First Leg Corner Radius: 0.220 inches  First Leg Distance Between Hole Centers Along Width: 0.870 inches  First Leg Distance From Edge To Hole Center Along Width: 0.530 inches  First Leg Distance From Edge To Hole Center Along Length: 0.220 inches  First Leg Style:

## **NSN 5340-00-735-0240** Angle Bracket - Page 2 of 2



Second Leg Style:
Corner radius
Second Leg Hole Arrangement Style:
Four holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Material:
Steel
Material Specification:
Qq-s-636 cond4or5 federal specification single material response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0