

View Online at <https://aerobasegroup.com/nsn/5340-00-737-9014>

**First Leg Length:**

Between 0.870 inches and 0.910 inches

**Second Leg Length:**

Between 3.576 inches and 3.616 inches

**Second Leg Width:**

Between 0.490 inches and 0.510 inches

**First Leg Hole Diameter:**

Between 0.276 inches and 0.286 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.245 inches and 0.255 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.479 inches and 0.544 inches

**Second Leg Slot Length:**

Between 0.370 inches and 0.380 inches

**Second Leg Slot Width:**

Between 0.214 inches and 0.224 inches

**First Leg Thickness:**

Between 0.071 inches and 0.085 inches

**Second Leg Thickness:**

Between 0.071 inches and 0.085 inches

**First Leg Width:**

Between 0.490 inches and 0.510 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.240 inches and 0.260 inches

**First Leg End Radius:**

Between 0.344 inches and 0.406 inches

**Second Leg End Radius:**

Between 0.344 inches and 0.406 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One slot

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

76.0 degrees

**Material:**

Steel comp 410

**Material Specification:**

Ams 5504 assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0