

View Online at <https://aerobasegroup.com/nsn/5340-00-753-8701>

Cross Sectional Shape:

Circular recess

Inside Diameter:

2.875 inches

Hole Diameter:

Between 0.344 inches and 0.359 inches

Width:

6.125 inches

Flange Thickness:

0.105 inches

Edge Shape:

Rectangle, multi holes

Length:

7.000 inches

Corner Radius:

0.375 inches

Hole Quantity Along Length:

2

Hole Quantity Along Width:

4

Distance Between Holes Along Length:

3.937 inches

Distance Between Holes Along Width:

5.375 inches

Distance From First Hole Centerline To End Along Length:

0.375 inches

Distance From First Hole Centerline To End Along Width:

0.375 inches

First Recess Inside Height:

0.250 inches

Inside Corner Radius:

0.125 inches

Body Thickness:

0.105 inches

Outside Corner Radius:

0.125 inches

Body Outside Radius:

0.125 inches

Securing Device Type:

Threaded fastener

Mounting Opening Shape Style:

Unthreaded hole

Special Features:

Sides along length periphery narrow to 5.125 in. Width, with 2.000 in. Outside radius and 0.500 in. Inverted radius connecting the two levels and periphery change beginning 4.062 in. From end, center of recess is on length centerline and 3.062 in. From end of wide width area, two pair 0.128 @min @0.131 maximum in. Diameter holes located 1.562 in. On either side of length centerline, 1.625 in. C to c @distance between holes of each pair w/first holes 0.500 in. From end of narrowed width of cover, 0.438 in. Outside corner radius on narrow width end of cover

Material:

Steel

Fsc Application Data:

Brake case winch, vehicular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A531c0