

View Online at <https://aerobasegroup.com/nsn/5340-00-753-8701>

**Cross Sectional Shape:**

Circular recess

**Inside Diameter:**

2.875 inches

**Hole Diameter:**

Between 0.344 inches and 0.359 inches

**Width:**

6.125 inches

**Flange Thickness:**

0.105 inches

**Edge Shape:**

Rectangle, multi holes

**Length:**

7.000 inches

**Corner Radius:**

0.375 inches

**Hole Quantity Along Length:**

2

**Hole Quantity Along Width:**

4

**Distance Between Holes Along Length:**

3.937 inches

**Distance Between Holes Along Width:**

5.375 inches

**Distance From First Hole Centerline To End Along Length:**

0.375 inches

**Distance From First Hole Centerline To End Along Width:**

0.375 inches

**First Recess Inside Height:**

0.250 inches

**Inside Corner Radius:**

0.125 inches

**Body Thickness:**

0.105 inches

**Outside Corner Radius:**

0.125 inches

**Body Outside Radius:**

0.125 inches

**Securing Device Type:**

Threaded fastener

**Mounting Opening Shape Style:**

Unthreaded hole

**Special Features:**

Sides along length periphery narrow to 5.125 in. Width, with 2.000 in. Outside radius and 0.500 in. Inverted radius connecting the two levels and periphery change beginning 4.062 in. From end, center of recess is on length centerline and 3.062 in. From end of wide width area, two pair 0.128 @min @0.131 maximum in. Diameter holes located 1.562 in. On either side of length centerline, 1.625 in. C to c @distance between holes of each pair w/first holes 0.500 in. From end of narrowed width of cover, 0.438 in. Outside corner radius on narrow width end of cover

**Material:**

Steel

**Fsc Application Data:**

Brake case winch, vehicular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A531c0