

View Online at <https://aerobasegroup.com/nsn/5340-00-754-1735>

Fabrication Method (non-core):

Any acceptable

Mounting Hole Type:

Plain

First Leg Length:

1.000 inches

Second Leg Length:

1.500 inches

Second Leg Width:

Between 1.219 inches and 1.281 inches

First Leg Hole Diameter:

Between 0.219 inches and 0.233 inches

Second Leg Hole Diameter:

Between 0.140 inches and 0.152 inches

Second Leg Distance Between Hole Centers Along Width:

0.719 inches

Second Leg Distance Between Hole Centers Along Length:

0.719 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.265 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.266 inches

First Leg Thickness:

Between 0.053 inches and 0.073 inches

Second Leg Thickness:

Between 0.073 inches and 0.083 inches

First Leg Width:

Between 1.219 inches and 1.281 inches

First Leg Distance Between Hole Centers Along Width:

0.625 inches

First Leg Distance From Edge To Hole Center Along Width:

0.312 inches

First Leg Distance From Edge To Hole Center Along Length:

0.375 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

One additional hole in second leg, 0.750 in. Dia

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-362, t3 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-s-5002 military specification single treatment response or mil-c-5541 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-s-5002 spec.