NSN 5340-00-754-1735

Angle Bracket - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5340-00-754-1735

Fabrication Method (non-core): Any acceptable Mounting Hole Type: Plain First Leg Length: 1.000 inches Second Leg Length: 1.500 inches Second Leg Width: Between 1.219 inches and 1.281 inches First Leg Hole Diameter: Between 0.219 inches and 0.233 inches Second Leg Hole Diameter: Between 0.140 inches and 0.152 inches Second Leg Distance Between Hole Centers Along Width: 0.719 inches Second Leg Distance Between Hole Centers Along Length: 0.719 inches Second Leg Distance From Edge To Hole Center Along Width: 0.265 inches Second Leg Distance From Edge To Hole Center Along Length: 0.266 inches First Leg Thickness: Between 0.053 inches and 0.073 inches Second Leg Thickness: Between 0.073 inches and 0.083 inches First Leg Width: Between 1.219 inches and 1.281 inches First Leg Distance Between Hole Centers Along Width: 0.625 inches First Leg Distance From Edge To Hole Center Along Width: 0.312 inches First Leg Distance From Edge To Hole Center Along Length: 0.375 inches First Leg Style: Square First Leg Hole Arrangement Style: Two holes Second Leg Style: Square Second Leg Hole Arrangement Style: Four holes



# NSN 5340-00-754-1735

Angle Bracket - Page 2 of 2



# Second Leg Relationship To First Leg:

Not identical

#### First Leg Angle:

90.0 degrees

# **Special Features:**

One additional hole in second leg, 0.750 in. Dia

#### Material:

Aluminum alloy 2024

## **Material Specification:**

Qq-a-362, t3 federal specification single material response

#### Surface Treatment:

Chromate

#### Surface Treatment Specification:

Mil-s-5002 military specification single treatment response or mil-c-5541 military specification single treatment response

## Style Designator:

Angle

# Shelf Life:

N/a

## Unit Of Measure:

# Demilitarization:

No

---

Fiig:

A042a0

#### Mil-std (military Standard):

Mil-s-5002 spec.