

View Online at <https://aerobasegroup.com/nsn/5340-00-754-1738>

Fabrication Method (non-core):

Stamped

First Leg Length:

Between 2.969 inches and 3.031 inches

Second Leg Length:

Between 0.844 inches and 0.906 inches

Second Leg Width:

Between 0.719 inches and 0.781 inches

Second Leg Corner Radius:

Between 0.094 inches and 0.156 inches

First Leg Hole Diameter:

Between 0.251 inches and 0.257 inches

Second Leg Hole Diameter:

Between 0.193 inches and 0.208 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.344 inches and 0.406 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.344 inches and 0.406 inches

First Leg Thickness:

0.063 inches

Second Leg Thickness:

0.063 inches

First Leg Width:

Between 0.719 inches and 0.781 inches

First Leg Corner Radius:

Between 0.094 inches and 0.156 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.344 inches and 0.406 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.281 inches and 0.344 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Furnished with one nut, plain, blind rivet

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/5, alclad t3 federal specification single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0