

View Online at <https://aerobasegroup.com/nsn/5340-00-754-1738>

**Fabrication Method (non-core):**

Stamped

**First Leg Length:**

Between 2.969 inches and 3.031 inches

**Second Leg Length:**

Between 0.844 inches and 0.906 inches

**Second Leg Width:**

Between 0.719 inches and 0.781 inches

**Second Leg Corner Radius:**

Between 0.094 inches and 0.156 inches

**First Leg Hole Diameter:**

Between 0.251 inches and 0.257 inches

**Second Leg Hole Diameter:**

Between 0.193 inches and 0.208 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.344 inches and 0.406 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.344 inches and 0.406 inches

**First Leg Thickness:**

0.063 inches

**Second Leg Thickness:**

0.063 inches

**First Leg Width:**

Between 0.719 inches and 0.781 inches

**First Leg Corner Radius:**

Between 0.094 inches and 0.156 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.344 inches and 0.406 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.281 inches and 0.344 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Furnished with one nut, plain, blind rivet

**Material:**

Aluminum alloy 2024

**Material Specification:**

Qq-a-250/5, alclad t3 federal specification single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0