NSN 5340-00-756-5066

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-756-5066

Fabrication Method (non-core): Machined First Leg Length: 1.120 inches Second Leg Length: 4.950 inches First Leg Hole Diameter: Between 0.256 inches and 0.263 inches Second Leg Hole Diameter: Between 0.249 inches and 0.255 inches First Leg Thickness: Between 0.115 inches and 0.155 inches Second Leg Thickness: Between 0.115 inches and 0.155 inches First Leg Width: 3.980 inches First Leg Corner Radius: 0.280 inches First Leg Distance Between First And Second Hole Centers Along Width: 1.000 inches First Leg Distance From Edge To Hole Center Along Width:
First Leg Length: 1.120 inches Second Leg Length: 4.950 inches First Leg Hole Diameter: Between 0.256 inches and 0.263 inches Second Leg Hole Diameter: Between 0.249 inches and 0.255 inches First Leg Thickness: Between 0.115 inches and 0.155 inches Second Leg Thickness: Between 0.115 inches and 0.155 inches First Leg Width: 3.980 inches First Leg Corner Radius: 0.280 inches First Leg Distance Between First And Second Hole Centers Along Width: 1.000 inches First Leg Distance Between Second And Third Hole Centers Along Width: 1.000 inches
1.120 inches Second Leg Length: 4.950 inches First Leg Hole Diameter: Between 0.256 inches and 0.263 inches Second Leg Hole Diameter: Between 0.249 inches and 0.255 inches First Leg Thickness: Between 0.115 inches and 0.155 inches Second Leg Thickness: Between 0.115 inches and 0.155 inches First Leg Width: 3.980 inches First Leg Corner Radius: 0.280 inches First Leg Distance Between First And Second Hole Centers Along Width: 1.000 inches First Leg Distance Between Second And Third Hole Centers Along Width: 1.000 inches
Second Leg Length: 4.950 inches First Leg Hole Diameter: Between 0.256 inches and 0.263 inches Second Leg Hole Diameter: Between 0.249 inches and 0.255 inches First Leg Thickness: Between 0.115 inches and 0.155 inches Second Leg Thickness: Between 0.115 inches and 0.155 inches First Leg Width: 3.980 inches First Leg Corner Radius: 0.280 inches First Leg Distance Between First And Second Hole Centers Along Width: 1.000 inches First Leg Distance Between Second And Third Hole Centers Along Width: 1.000 inches
4.950 inches First Leg Hole Diameter: Between 0.256 inches and 0.263 inches Second Leg Hole Diameter: Between 0.249 inches and 0.255 inches First Leg Thickness: Between 0.115 inches and 0.155 inches Second Leg Thickness: Between 0.115 inches and 0.155 inches First Leg Width: 3.980 inches First Leg Corner Radius: 0.280 inches First Leg Distance Between First And Second Hole Centers Along Width: 1.000 inches First Leg Distance Between Second And Third Hole Centers Along Width: 1.000 inches
First Leg Hole Diameter: Between 0.256 inches and 0.263 inches Second Leg Hole Diameter: Between 0.249 inches and 0.255 inches First Leg Thickness: Between 0.115 inches and 0.155 inches Second Leg Thickness: Between 0.115 inches and 0.155 inches First Leg Width: 3.980 inches First Leg Corner Radius: 0.280 inches First Leg Distance Between First And Second Hole Centers Along Width: 1.000 inches First Leg Distance Between Second And Third Hole Centers Along Width: 1.000 inches
Between 0.256 inches and 0.263 inches Second Leg Hole Diameter: Between 0.249 inches and 0.255 inches First Leg Thickness: Between 0.115 inches and 0.155 inches Second Leg Thickness: Between 0.115 inches and 0.155 inches First Leg Width: 3.980 inches First Leg Corner Radius: 0.280 inches First Leg Distance Between First And Second Hole Centers Along Width: 1.000 inches First Leg Distance Between Second And Third Hole Centers Along Width: 1.000 inches
Second Leg Hole Diameter: Between 0.249 inches and 0.255 inches First Leg Thickness: Between 0.115 inches and 0.155 inches Second Leg Thickness: Between 0.115 inches and 0.155 inches First Leg Width: 3.980 inches First Leg Corner Radius: 0.280 inches First Leg Distance Between First And Second Hole Centers Along Width: 1.000 inches First Leg Distance Between Second And Third Hole Centers Along Width: 1.000 inches
Between 0.249 inches and 0.255 inches First Leg Thickness: Between 0.115 inches and 0.155 inches Second Leg Thickness: Between 0.115 inches and 0.155 inches First Leg Width: 3.980 inches First Leg Corner Radius: 0.280 inches First Leg Distance Between First And Second Hole Centers Along Width: 1.000 inches First Leg Distance Between Second And Third Hole Centers Along Width: 1.000 inches
First Leg Thickness: Between 0.115 inches and 0.155 inches Second Leg Thickness: Between 0.115 inches and 0.155 inches First Leg Width: 3.980 inches First Leg Corner Radius: 0.280 inches First Leg Distance Between First And Second Hole Centers Along Width: 1.000 inches First Leg Distance Between Second And Third Hole Centers Along Width: 1.000 inches
Between 0.115 inches and 0.155 inches Second Leg Thickness: Between 0.115 inches and 0.155 inches First Leg Width: 3.980 inches First Leg Corner Radius: 0.280 inches First Leg Distance Between First And Second Hole Centers Along Width: 1.000 inches First Leg Distance Between Second And Third Hole Centers Along Width: 1.000 inches
Second Leg Thickness: Between 0.115 inches and 0.155 inches First Leg Width: 3.980 inches First Leg Corner Radius: 0.280 inches First Leg Distance Between First And Second Hole Centers Along Width: 1.000 inches First Leg Distance Between Second And Third Hole Centers Along Width: 1.000 inches
Between 0.115 inches and 0.155 inches First Leg Width: 3.980 inches First Leg Corner Radius: 0.280 inches First Leg Distance Between First And Second Hole Centers Along Width: 1.000 inches First Leg Distance Between Second And Third Hole Centers Along Width: 1.000 inches
First Leg Width: 3.980 inches First Leg Corner Radius: 0.280 inches First Leg Distance Between First And Second Hole Centers Along Width: 1.000 inches First Leg Distance Between Second And Third Hole Centers Along Width: 1.000 inches
3.980 inches First Leg Corner Radius: 0.280 inches First Leg Distance Between First And Second Hole Centers Along Width: 1.000 inches First Leg Distance Between Second And Third Hole Centers Along Width: 1.000 inches
First Leg Corner Radius: 0.280 inches First Leg Distance Between First And Second Hole Centers Along Width: 1.000 inches First Leg Distance Between Second And Third Hole Centers Along Width: 1.000 inches
0.280 inches First Leg Distance Between First And Second Hole Centers Along Width: 1.000 inches First Leg Distance Between Second And Third Hole Centers Along Width: 1.000 inches
First Leg Distance Between First And Second Hole Centers Along Width: 1.000 inches First Leg Distance Between Second And Third Hole Centers Along Width: 1.000 inches
1.000 inches First Leg Distance Between Second And Third Hole Centers Along Width: 1.000 inches
First Leg Distance Between Second And Third Hole Centers Along Width: 1.000 inches
1.000 inches
First Leg Distance From Edge To Hole Center Along Width:
1.360 inches
First Leg Distance From Edge To Hole Center Along Length:
0.545 inches
First Leg Style:
Corner radius
First Leg Hole Arrangement Style:
Three holes
Second Leg Hole Arrangement Style:
Two holes
First Leg Angle:
77.0 degrees
Material:
Aluminum alloy
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:

-

NSN 5340-00-756-5066

Angle Bracket - Page 2 of 2



Demilitarization:

No

Fiig:

A042a0