NSN 5340-00-757-5681

Rod End Clevis - Page 1 of 2

Unjf rod connection



View Online at https://aerobasegroup.com/nsn/5340-00-757-5681

| Thread Class: |
|--|
| 3b rod connection |
| Thread Direction: |
| Right-hand rod connection |
| Thread Length: |
| 0.590 inches rod connection and 0.650 inches rod connection |
| Shank Length: |
| 0.460 inches |
| Hole Diameter: |
| Between 0.2490 inches and 0.2505 inches |
| Shank Diameter: |
| 0.500 inches |
| Overall Width: |
| Between 0.447 inches and 0.452 inches |
| End Radius: |
| 0.312 inches |
| Fork Span Width: |
| Between 0.2075 inches and 0.212 inches |
| Distance From Pivot Pinhole Center To Rod Connection End: |
| 1.300 inches |
| Fork Arm Thickness: |
| 0.120 inches |
| Fork Depth: |
| 0.420 inches |
| Shank Shoulder Diameter: |
| 0.625 inches |
| Thread Size: |
| 0.312 inches rod connection |
| Criticality Code Justification: |
| Aaub |
| Material: |
| Steel comp 4140 |
| Material Specification: |
| Mil-s-5626 military specification single material response and ams 6382 assn standard single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Cp-0480, type 2, the bendix corporation mfr ref single treatment response |
| Style Designator: |
| Clevis |
| Thread Series Designator: |

NSN 5340-00-757-5681

Rod End Clevis - Page 2 of 2



| Shelf Life: |
|-------------------|
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| |

Mil-std (military Standard):

Mil-s-5626 spec.