

View Online at <https://aerobasegroup.com/nsn/5340-00-757-8265>

Fabrication Method (non-core):

Stamped

First Leg Length:

Between 0.860 inches and 0.880 inches

Second Leg Length:

Between 0.860 inches and 0.880 inches

Second Leg Width:

Between 0.480 inches and 0.520 inches

First Leg Hole Diameter:

Between 0.214 inches and 0.224 inches

Second Leg Hole Diameter:

Between 0.214 inches and 0.224 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg Thickness:

Between 0.056 inches and 0.068 inches

Second Leg Thickness:

Between 0.056 inches and 0.068 inches

Center Section Height:

Between 0.346 inches and 0.378 inches

Center Section Width:

Between 0.480 inches and 0.520 inches

Center Section Thickness:

Between 0.056 inches and 0.068 inches

First Leg Width:

Between 0.480 inches and 0.520 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg End Radius:

Between 0.344 inches and 0.406 inches

Second Leg End Radius:

Between 0.344 inches and 0.406 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

135.0 degrees

Second Leg Angle:

135.0 degrees

Material:

Steel comp 410

Material Specification:

Ams 5504 assn standard single material response

Surface Treatment:

Passivate

Style Designator:

Double angle

Fsc Application Data:

Engine, acft, turbo-jet

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

FiiG:

A042a0