
Access Cover - Page 1 of 2





Cross Sectional Shape:

Oblong recess

Hole Diameter:

0.281 inches

Width:

5.375 inches

Flange Thickness:

0.250 inches

Edge Shape:

Rectangle, multi holes

Length:

7.250 inches

Inside Width:

3.875 inches

Inside Length:

5.750 inches

Corner Radius:

1.000 inches

Hole Quantity Along Length:

4

Hole Quantity Along Width:

6

Distance Between Holes Along Length:

2.104 inches

Distance Between Holes Along Width:

2.217 inches

Distance Between Hole Centerline And First Hole Along Length:

2.323 inches

Distance Between Hole Centerline And First Hole Along Width:

2.437 inches

Distance From First Hole Centerline To End Along Length:

2.543 inches

Distance From First Hole Centerline To End Along Width:

2.657 inches

Corner Hole Centerline Radius:

1.000 inches

First Recess Inside Height:

0.125 inches

Inside Corner Radius:

0.125 inches

Body Thickness:

0.250 inches

NSN 5340-00-763-4321

Access Cover - Page 2 of 2



Outside Corner Radius:

0.125 inches

Body Outside Radius:

0.375 inches

Securing Device Type:

Threaded fastener

Mounting Opening Shape Style:

Unthreaded hole

Inside Angle:

90.0 degrees

Material:

Aluminum alloy

Fsc Application Data:

Fire control designating and indicating equipment

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A531c0