

View Online at <https://aerobasegroup.com/nsn/5340-00-774-9463>

Thread Class:

3b rod connection

Thread Direction:

Right-hand rod connection

Thread Length:

1.255 inches rod connection

Shank Length:

Between 0.520 inches and 0.580 inches

Hole Diameter:

Between 0.8742 inches and 0.8747 inches

Shank Diameter:

Between 1.830 inches and 1.850 inches

Overall Height:

Between 1.865 inches and 1.885 inches

Overall Width:

Between 2.940 inches and 2.983 inches

Angle Height:

Between 0.490 inches and 0.510 inches

Fork Span Width:

Between 1.960 inches and 1.963 inches

Distance From Pivot Pinhole Center To Rod Connection End:

Between 4.355 inches and 4.395 inches

Fork Arm Thickness:

0.490 mils and 0.510 centimeters

Fork Depth:

Between 3.090 inches and 3.150 inches

Thread Size:

1.500 inches rod connection

Angle:

45.0 degrees

Material:

Steel comp 4130 or steel

Material Specification:

Mil-s-6758, cond c1 military specification 1st material response or 299-947-055, bell helicopter co mfr ref 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

299-099-031, cb2, bell helicopter co mfr ref single treatment response

Style Designator:

Clevis

Thread Series Designator:

Unef rod connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A264a0

Mil-std (military Standard):

Mil-s-6758 spec.