

View Online at <https://aerobasegroup.com/nsn/5340-00-775-6511>

**First Leg Length:**

Between 0.710 inches and 0.730 inches

**Second Leg Length:**

Between 1.050 inches and 1.070 inches

**Second Leg Width:**

Between 0.490 inches and 0.510 inches

**First Leg Hole Diameter:**

Between 0.210 inches and 0.230 inches

**Second Leg Hole Diameter:**

Between 0.270 inches and 0.290 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.240 inches and 0.260 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.230 inches and 0.270 inches

**First Leg Thickness:**

Between 0.050 inches and 0.070 inches

**Second Leg Thickness:**

Between 0.050 inches and 0.070 inches

**First Leg Width:**

Between 0.490 inches and 0.510 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.240 inches and 0.260 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.230 inches and 0.270 inches

**First Leg End Radius:**

Between 0.300 inches and 0.320 inches

**Second Leg End Radius:**

Between 0.300 inches and 0.320 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 4130

**Material Specification:**

Ams 6350 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400-3 assn standard single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0