

View Online at <https://aerobasegroup.com/nsn/5340-00-778-8810>

Fabrication Method (non-core):

Stamped

Mounting Hole Type:

Plain

First Leg Length:

Between 1.719 inches and 1.781 inches

Second Leg Length:

Between 2.219 inches and 2.281 inches

Second Leg Width:

Between 2.969 inches and 3.031 inches

First Leg Hole Diameter:

Between 0.193 inches and 0.208 inches

Second Leg Hole Diameter:

Between 0.193 inches and 0.208 inches

Second Leg Distance Between Hole Centers Along Length:

Between 1.594 inches and 1.656 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.531 inches and 0.594 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.156 inches and 0.219 inches

First Leg Thickness:

Between 0.053 inches and 0.073 inches

Second Leg Thickness:

Between 0.053 inches and 0.073 inches

First Leg Width:

Between 2.969 inches and 3.031 inches

First Leg Distance Between Hole Centers Along Width:

Between 0.969 inches and 1.031 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 1.219 inches and 1.281 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.719 inches and 0.781 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Heat Treatment:

T-6 solution heat treated

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11, t6 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.