

View Online at <https://aerobasegroup.com/nsn/5340-00-779-7965>

Fabrication Method (non-core):

Machined

First Leg Length:

0.650 inches

Second Leg Length:

1.350 inches

Second Leg Width:

1.720 inches

First Leg Slot Length:

0.720 inches

First Leg Slot Width:

Between 0.200 inches and 0.206 inches

Second Leg Hole Diameter:

Between 0.199 inches and 0.204 inches

Second Leg Distance Between Lower Hole Centers Along Width:

1.100 inches

Second Leg Distance Between Hole Centers Along Length:

0.520 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

0.550 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.310 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.310 inches

First Leg Thickness:

0.180 inches

Second Leg Thickness:

0.100 inches

First Leg Width:

1.720 inches

First Leg Corner Radius:

0.310 inches

First Leg Distance From Edge To Hole Center Along Width:

0.860 inches

First Leg Distance From Edge To Hole Center Along Length:

0.419 inches

Second Leg End Radius:

0.310 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Heat Treatment:

Annealed

Material:

Steel comp 416

Material Specification:

Qq-s-763 federal specification single material response

Surface Treatment:

Cadmium

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0