

View Online at <https://aerobasegroup.com/nsn/5340-00-782-4605>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.820 inches and 0.840 inches

Second Leg Length:

Between 1.240 inches and 1.260 inches

Second Leg Width:

Between 0.620 inches and 0.640 inches

First Leg Slot Length:

Between 0.400 inches and 0.410 inches

First Leg Slot Width:

Between 0.320 inches and 0.330 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.310 inches and 0.320 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.265 inches and 0.290 inches

Second Leg Slot Length:

Between 0.285 inches and 0.290 inches

Second Leg Slot Width:

Between 0.200 inches and 0.210 inches

First Leg Thickness:

Between 0.057 inches and 0.069 inches

Second Leg Thickness:

Between 0.057 inches and 0.069 inches

First Leg Width:

Between 0.620 inches and 0.640 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.310 inches and 0.320 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.285 inches and 0.310 inches

First Leg End Radius:

Between 0.490 inches and 0.510 inches

Second Leg End Radius:

Between 0.490 inches and 0.510 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0