

View Online at <https://aerobasegroup.com/nsn/5340-00-789-0808>

Fabrication Method (non-core):

Stamped

First Leg Length:

Between 0.602 inches and 0.642 inches

Second Leg Length:

Between 4.980 inches and 5.020 inches

Second Leg Width:

Between 0.480 inches and 0.520 inches

First Leg Hole Diameter:

Between 0.268 inches and 0.271 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.230 inches and 0.270 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.225 inches and 0.265 inches

Second Leg Slot Length:

Between 0.350 inches and 0.390 inches

Second Leg Slot Width:

Between 0.194 inches and 0.204 inches

First Leg Thickness:

Between 0.059 inches and 0.065 inches

Second Leg Thickness:

Between 0.059 inches and 0.065 inches

Center Section Height:

Between 3.010 inches and 3.050 inches

Center Section Width:

Between 0.480 inches and 0.520 inches

Center Section Thickness:

Between 0.059 inches and 0.065 inches

First Leg Width:

Between 0.480 inches and 0.520 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.230 inches and 0.270 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.230 inches and 0.270 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

One slot

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Special Features:

Furnished with one nut, self-locking and one rubber strip

Heat Treatment:

H-14 strain hardened, 1/2 hard

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0