

View Online at <https://aerobasegroup.com/nsn/5340-00-789-1017>

First Leg Length:

4.000 inches

Second Leg Length:

8.000 inches

Reinforcement Method (non-core):

Gusset both legs

Second Leg Width:

6.000 inches

First Leg Hole Diameter:

0.500 inches

Second Leg Hole Diameter:

0.750 inches

Second Leg Distance From Edge To Hole Center Along Width:

3.000 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.000 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

6.000 inches

First Leg Distance Between Hole Centers Along Width:

3.875 inches

First Leg Distance From Edge To Hole Center Along Width:

1.062 inches

First Leg Distance From Edge To Hole Center Along Length:

0.312 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 1010

Material Specification:

Qq-s-741 federal specification single material response or qq-s-633 federal specification single material response

Surface Treatment:

Phosphate

Surface Treatment Specification:

Mil-p-16232, type m or z, class2 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-p-16232 spec.