

View Online at <https://aerobasegroup.com/nsn/5340-00-789-1017>

**First Leg Length:**

4.000 inches

**Second Leg Length:**

8.000 inches

**Reinforcement Method (non-core):**

Gusset both legs

**Second Leg Width:**

6.000 inches

**First Leg Hole Diameter:**

0.500 inches

**Second Leg Hole Diameter:**

0.750 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

3.000 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

1.000 inches

**First Leg Thickness:**

0.250 inches

**Second Leg Thickness:**

0.250 inches

**First Leg Width:**

6.000 inches

**First Leg Distance Between Hole Centers Along Width:**

3.875 inches

**First Leg Distance From Edge To Hole Center Along Width:**

1.062 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.312 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 1010

**Material Specification:**

Qq-s-741 federal specification single material response or qq-s-633 federal specification single material response

**Surface Treatment:**

Phosphate

**Surface Treatment Specification:**

Mil-p-16232, type m or z, class2 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-p-16232 spec.