NSN 5340-00-797-2619

Loop Clamp - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-797-2619

| Tongue Hole Type: Round, threaded Integral Nut Type And Quantity: 1 self-locking equal length tongues Cushioning Environmental Protection: Any acceptable Overall Width: 0.500 inches Material Thickness: Between 0.036 inches and 0.044 inches Lug Width: Any acceptable Center To Center Distance Between First And Second Holes: Between 1.219 inches and 1.281 inches Center To Center Distance Between Loop And Mounting Hole: 0.788 inches Distance From Loop Center To Tongue End: 1.163 inches Lug Hole Diameter: 0.500 inches Lug Hole Diameter: 0.204 inches 0.204 inches Thready Qty Per Inch (tpi): 33232 Thread Size: 0.190 inches0.190 inches |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Integral Nut Type And Quantity: 1 self-locking equal length tongues Cushioning Environmental Protection: Any acceptable Overall Width: 0.500 inches Material Thickness: Between 0.036 inches and 0.044 inches Lug Width: Any acceptable Center To Center Distance Between First And Second Holes: Between 1.219 inches and 1.281 inches Center To Center Distance Between Loop And Mounting Hole: 0.788 inches Distance From Loop Center To Tongue End: 1.163 inches Lug Hole Diameter: 0.204 inches 0.204 inches Thready Qty Per Inch (tpi): 32322 Thread Size: |
| 1 self-locking equal length tongues Cushioning Environmental Protection: Any acceptable Overall Width: 0.500 inches Material Thickness: Between 0.036 inches and 0.044 inches Lug Width: Any acceptable Center To Center Distance Between First And Second Holes: Between 1.219 inches and 1.281 inches Center To Center Distance Between Loop And Mounting Hole: 0.788 inches Distance From Loop Center To Tongue End: 1.163 inches Loop Inside Diameter: 0.500 inches Lug Hole Diameter: 0.204 inches 0.204 inches Thready Cty Per Inch (tpi): 32322 Thread Size: |
| Cushioning Environmental Protection: Any acceptable Overall Width: 0.500 inches Material Thickness: Between 0.036 inches and 0.044 inches Lug Width: Any acceptable Center To Center Distance Between First And Second Holes: Between 1.219 inches and 1.281 inches Center To Center Distance Between Loop And Mounting Hole: 0.788 inches Distance From Loop Center To Tongue End: 1.163 inches Loop Inside Diameter: 0.500 inches Lug Hole Diameter: 0.204 inches 0.204 inches Thready Qty Per Inch (tpi): 3232 Thread Size: |
| Any acceptable Overall Width: 0.500 inches Material Thickness: Between 0.036 inches and 0.044 inches Lug Width: Any acceptable Center To Center Distance Between First And Second Holes: Between 1.219 inches and 1.281 inches Center To Center Distance Between Loop And Mounting Hole: 0.788 inches Distance From Loop Center To Tongue End: 1.163 inches Loop Inside Diameter: 0.500 inches Lug Hole Diameter: 0.204 inches 0.204 inches Thready Qty Per Inch (tpi): 3232 Thread Size: |
| Overall Width: 0.500 inches Material Thickness: Between 0.036 inches and 0.044 inches Lug Width: Any acceptable Center To Center Distance Between First And Second Holes: Between 1.219 inches and 1.281 inches Center To Center Distance Between Loop And Mounting Hole: 0.788 inches Distance From Loop Center To Tongue End: 1.163 inches Loop Inside Diameter: 0.500 inches Lug Hole Diameter: 0.204 inches 0.204 inches Thready Qty Per Inch (tpi): 3232 Thread Size: |
| Material Thickness: Between 0.036 inches and 0.044 inches Lug Width: Any acceptable Center To Center Distance Between First And Second Holes: Between 1.219 inches and 1.281 inches Center To Center Distance Between Loop And Mounting Hole: 0.788 inches Distance From Loop Center To Tongue End: 1.163 inches Loop Inside Diameter: 0.500 inches Lug Hole Diameter: 0.204 inches 0.204 inches Thready Qty Per Inch (tpi): 3232 Thread Size: |
| Material Thickness: Between 0.036 inches and 0.044 inches Lug Width: Any acceptable Center To Center Distance Between First And Second Holes: Between 1.219 inches and 1.281 inches Center To Center Distance Between Loop And Mounting Hole: 0.788 inches Distance From Loop Center To Tongue End: 1.163 inches Loop Inside Diameter: 0.500 inches Lug Hole Diameter: 0.204 inches 0.204 inches Thready Qty Per Inch (tpi): 3232 Thread Size: |
| Between 0.036 inches and 0.044 inches Lug Width: Any acceptable Center To Center Distance Between First And Second Holes: Between 1.219 inches and 1.281 inches Center To Center Distance Between Loop And Mounting Hole: 0.788 inches Distance From Loop Center To Tongue End: 1.163 inches Loop Inside Diameter: 0.500 inches Lug Hole Diameter: 0.204 inches 0.204 inches Thready Qty Per Inch (tpi): 3232 Thread Size: |
| Lug Width: Any acceptable Center To Center Distance Between First And Second Holes: Between 1.219 inches and 1.281 inches Center To Center Distance Between Loop And Mounting Hole: 0.788 inches Distance From Loop Center To Tongue End: 1.163 inches Loop Inside Diameter: 0.500 inches Lug Hole Diameter: 0.204 inches 0.204 inches Thready Qty Per Inch (tpi): 3232 Thread Size: |
| Any acceptable Center To Center Distance Between First And Second Holes: Between 1.219 inches and 1.281 inches Center To Center Distance Between Loop And Mounting Hole: 0.788 inches Distance From Loop Center To Tongue End: 1.163 inches Loop Inside Diameter: 0.500 inches Lug Hole Diameter: 0.204 inches 0.204 inches Thready Qty Per Inch (tpi): 3232 Thread Size: |
| Center To Center Distance Between First And Second Holes: Between 1.219 inches and 1.281 inches Center To Center Distance Between Loop And Mounting Hole: 0.788 inches Distance From Loop Center To Tongue End: 1.163 inches Loop Inside Diameter: 0.500 inches Lug Hole Diameter: 0.204 inches 0.204 inches Thready Qty Per Inch (tpi): 3232 Thread Size: |
| Between 1.219 inches and 1.281 inches Center To Center Distance Between Loop And Mounting Hole: 0.788 inches Distance From Loop Center To Tongue End: 1.163 inches Loop Inside Diameter: 0.500 inches Lug Hole Diameter: 0.204 inches 0.204 inches Thready Qty Per Inch (tpi): 3232 Thread Size: |
| Center To Center Distance Between Loop And Mounting Hole: 0.788 inches Distance From Loop Center To Tongue End: 1.163 inches Loop Inside Diameter: 0.500 inches Lug Hole Diameter: 0.204 inches 0.204 inches Thready Qty Per Inch (tpi): 3232 Thread Size: |
| 0.788 inches Distance From Loop Center To Tongue End: 1.163 inches Loop Inside Diameter: 0.500 inches Lug Hole Diameter: 0.204 inches 0.204 inches Thready Qty Per Inch (tpi): 3232 Thread Size: |
| Distance From Loop Center To Tongue End: 1.163 inches Loop Inside Diameter: 0.500 inches Lug Hole Diameter: 0.204 inches 0.204 inches Thready Qty Per Inch (tpi): 3232 Thread Size: |
| 1.163 inches Loop Inside Diameter: 0.500 inches Lug Hole Diameter: 0.204 inches 0.204 inches Thready Qty Per Inch (tpi): 3232 Thread Size: |
| Loop Inside Diameter: 0.500 inches Lug Hole Diameter: 0.204 inches 0.204 inches Thready Qty Per Inch (tpi): 3232 Thread Size: |
| 0.500 inches Lug Hole Diameter: 0.204 inches 0.204 inches Thready Qty Per Inch (tpi): 3232 Thread Size: |
| Lug Hole Diameter: 0.204 inches 0.204 inches Thready Qty Per Inch (tpi): 3232 Thread Size: |
| 0.204 inches 0.204 inches Thready Qty Per Inch (tpi): 3232 Thread Size: |
| Thready Qty Per Inch (tpi): 3232 Thread Size: |
| 3232 Thread Size: |
| Thread Size: |
| |
| 2.100 inchas0.100 inchas |
| 3.130 Inches0.130 Inches |
| Special Features: |
| Single mtg right footsingle mtg right foot |
| Material: |
| Stainless steel bandstainless steel band |
| Material Specification: |
| Mil-s-6721 military specification single material response bandmil-s-6721 military specification single material response band |
| Surface Treatment: |
| Passivate bandpassivate band |
| Style Designator: |
| Clamp & bracketclamp & bracket |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5340-00-797-2619

Loop Clamp - Page 2 of 2



Fiig:

A12700

Mil-std (military Standard):

Mil-s-6721 spec.