## NSN 5340-00-797-2619

Loop Clamp - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-797-2619

Tongue Hole Type: Round, threaded Integral Nut Type And Quantity: 1 self-locking equal length tongues Cushioning Environmental Protection: Any acceptable Overall Width: 0.500 inches Material Thickness: Between 0.036 inches and 0.044 inches Lug Width: Any acceptable Center To Center Distance Between First And Second Holes: Between 1.219 inches and 1.281 inches Center To Center Distance Between Loop And Mounting Hole: 0.788 inches Distance From Loop Center To Tongue End: 1.163 inches Lug Hole Diameter: 0.500 inches Lug Hole Diameter: 0.204 inches 0.204 inches Thready Qty Per Inch (tpi): 33232 Thread Size: 0.190 inches0.190 inches
Integral Nut Type And Quantity:  1 self-locking equal length tongues  Cushioning Environmental Protection:  Any acceptable  Overall Width:  0.500 inches  Material Thickness:  Between 0.036 inches and 0.044 inches  Lug Width:  Any acceptable  Center To Center Distance Between First And Second Holes:  Between 1.219 inches and 1.281 inches  Center To Center Distance Between Loop And Mounting Hole:  0.788 inches  Distance From Loop Center To Tongue End:  1.163 inches  Lug Hole Diameter:  0.204 inches 0.204 inches  Thready Qty Per Inch (tpi):  32322  Thread Size:
1 self-locking equal length tongues  Cushioning Environmental Protection:  Any acceptable  Overall Width: 0.500 inches  Material Thickness:  Between 0.036 inches and 0.044 inches  Lug Width:  Any acceptable  Center To Center Distance Between First And Second Holes:  Between 1.219 inches and 1.281 inches  Center To Center Distance Between Loop And Mounting Hole: 0.788 inches  Distance From Loop Center To Tongue End: 1.163 inches  Loop Inside Diameter: 0.500 inches  Lug Hole Diameter: 0.204 inches 0.204 inches  Thready Cty Per Inch (tpi): 32322  Thread Size:
Cushioning Environmental Protection:  Any acceptable  Overall Width: 0.500 inches  Material Thickness: Between 0.036 inches and 0.044 inches Lug Width: Any acceptable  Center To Center Distance Between First And Second Holes: Between 1.219 inches and 1.281 inches  Center To Center Distance Between Loop And Mounting Hole: 0.788 inches  Distance From Loop Center To Tongue End: 1.163 inches  Loop Inside Diameter: 0.500 inches  Lug Hole Diameter: 0.204 inches 0.204 inches  Thready Qty Per Inch (tpi): 3232  Thread Size:
Any acceptable Overall Width: 0.500 inches Material Thickness: Between 0.036 inches and 0.044 inches Lug Width: Any acceptable Center To Center Distance Between First And Second Holes: Between 1.219 inches and 1.281 inches Center To Center Distance Between Loop And Mounting Hole: 0.788 inches Distance From Loop Center To Tongue End: 1.163 inches Loop Inside Diameter: 0.500 inches Lug Hole Diameter: 0.204 inches 0.204 inches Thready Qty Per Inch (tpi): 3232 Thread Size:
Overall Width:  0.500 inches  Material Thickness: Between 0.036 inches and 0.044 inches Lug Width: Any acceptable Center To Center Distance Between First And Second Holes: Between 1.219 inches and 1.281 inches Center To Center Distance Between Loop And Mounting Hole: 0.788 inches Distance From Loop Center To Tongue End: 1.163 inches Loop Inside Diameter: 0.500 inches Lug Hole Diameter: 0.204 inches 0.204 inches Thready Qty Per Inch (tpi): 3232 Thread Size:
Material Thickness: Between 0.036 inches and 0.044 inches Lug Width: Any acceptable Center To Center Distance Between First And Second Holes: Between 1.219 inches and 1.281 inches Center To Center Distance Between Loop And Mounting Hole: 0.788 inches Distance From Loop Center To Tongue End: 1.163 inches Loop Inside Diameter: 0.500 inches Lug Hole Diameter: 0.204 inches 0.204 inches Thready Qty Per Inch (tpi): 3232 Thread Size:
Material Thickness: Between 0.036 inches and 0.044 inches Lug Width: Any acceptable Center To Center Distance Between First And Second Holes: Between 1.219 inches and 1.281 inches Center To Center Distance Between Loop And Mounting Hole: 0.788 inches Distance From Loop Center To Tongue End: 1.163 inches Loop Inside Diameter: 0.500 inches Lug Hole Diameter: 0.204 inches 0.204 inches Thready Qty Per Inch (tpi): 3232 Thread Size:
Between 0.036 inches and 0.044 inches  Lug Width: Any acceptable  Center To Center Distance Between First And Second Holes: Between 1.219 inches and 1.281 inches  Center To Center Distance Between Loop And Mounting Hole: 0.788 inches  Distance From Loop Center To Tongue End: 1.163 inches  Loop Inside Diameter: 0.500 inches  Lug Hole Diameter: 0.204 inches 0.204 inches  Thready Qty Per Inch (tpi): 3232  Thread Size:
Lug Width: Any acceptable Center To Center Distance Between First And Second Holes: Between 1.219 inches and 1.281 inches Center To Center Distance Between Loop And Mounting Hole: 0.788 inches Distance From Loop Center To Tongue End: 1.163 inches Loop Inside Diameter: 0.500 inches Lug Hole Diameter: 0.204 inches 0.204 inches Thready Qty Per Inch (tpi): 3232 Thread Size:
Any acceptable  Center To Center Distance Between First And Second Holes:  Between 1.219 inches and 1.281 inches  Center To Center Distance Between Loop And Mounting Hole: 0.788 inches  Distance From Loop Center To Tongue End: 1.163 inches  Loop Inside Diameter: 0.500 inches  Lug Hole Diameter: 0.204 inches 0.204 inches  Thready Qty Per Inch (tpi): 3232  Thread Size:
Center To Center Distance Between First And Second Holes: Between 1.219 inches and 1.281 inches  Center To Center Distance Between Loop And Mounting Hole: 0.788 inches  Distance From Loop Center To Tongue End: 1.163 inches  Loop Inside Diameter: 0.500 inches  Lug Hole Diameter: 0.204 inches 0.204 inches  Thready Qty Per Inch (tpi): 3232  Thread Size:
Between 1.219 inches and 1.281 inches  Center To Center Distance Between Loop And Mounting Hole: 0.788 inches  Distance From Loop Center To Tongue End: 1.163 inches  Loop Inside Diameter: 0.500 inches  Lug Hole Diameter: 0.204 inches 0.204 inches  Thready Qty Per Inch (tpi): 3232  Thread Size:
Center To Center Distance Between Loop And Mounting Hole: 0.788 inches Distance From Loop Center To Tongue End: 1.163 inches Loop Inside Diameter: 0.500 inches Lug Hole Diameter: 0.204 inches 0.204 inches Thready Qty Per Inch (tpi): 3232 Thread Size:
0.788 inches  Distance From Loop Center To Tongue End:  1.163 inches  Loop Inside Diameter:  0.500 inches  Lug Hole Diameter:  0.204 inches 0.204 inches  Thready Qty Per Inch (tpi):  3232  Thread Size:
Distance From Loop Center To Tongue End:  1.163 inches  Loop Inside Diameter:  0.500 inches  Lug Hole Diameter:  0.204 inches 0.204 inches  Thready Qty Per Inch (tpi):  3232  Thread Size:
1.163 inches  Loop Inside Diameter: 0.500 inches  Lug Hole Diameter: 0.204 inches 0.204 inches  Thready Qty Per Inch (tpi): 3232  Thread Size:
Loop Inside Diameter:  0.500 inches  Lug Hole Diameter:  0.204 inches 0.204 inches  Thready Qty Per Inch (tpi):  3232  Thread Size:
0.500 inches  Lug Hole Diameter: 0.204 inches 0.204 inches  Thready Qty Per Inch (tpi): 3232  Thread Size:
Lug Hole Diameter:  0.204 inches 0.204 inches  Thready Qty Per Inch (tpi):  3232  Thread Size:
0.204 inches 0.204 inches  Thready Qty Per Inch (tpi): 3232  Thread Size:
Thready Qty Per Inch (tpi): 3232 Thread Size:
3232 Thread Size:
Thread Size:
2.100 inchas0.100 inchas
3.130 Inches0.130 Inches
Special Features:
Single mtg right footsingle mtg right foot
Material:
Stainless steel bandstainless steel band
Material Specification:
Mil-s-6721 military specification single material response bandmil-s-6721 military specification single material response band
Surface Treatment:
Passivate bandpassivate band
Style Designator:
Clamp & bracketclamp & bracket
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:

No

## NSN 5340-00-797-2619

Loop Clamp - Page 2 of 2



Fiig:

A12700

Mil-std (military Standard):

Mil-s-6721 spec.