

View Online at <https://aerobasegroup.com/nsn/5340-00-798-8151>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.630 inches and 0.710 inches

Second Leg Length:

Between 0.630 inches and 0.710 inches

Second Leg Width:

Between 2.910 inches and 3.010 inches

Second Leg Corner Radius:

Between 0.230 inches and 0.270 inches

First Leg Hole Diameter:

0.219 inches

Second Leg Hole Diameter:

0.281 inches

Second Leg Distance Between Hole Centers Along Width:

Between 2.450 inches and 2.470 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.230 inches and 0.270 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.230 inches and 0.270 inches

First Leg Thickness:

Between 0.057 inches and 0.069 inches

Second Leg Thickness:

Between 0.057 inches and 0.069 inches

Center Section Height:

Between 0.990 inches and 1.030 inches

Center Section Thickness:

Between 0.057 inches and 0.069 inches

First Leg Width:

Between 0.460 inches and 0.540 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.230 inches and 0.270 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.230 inches and 0.270 inches

First Leg End Radius:

Between 0.230 inches and 0.270 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0