

View Online at <https://aerobasegroup.com/nsn/5340-00-798-9186>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.845 inches and 0.895 inches

Second Leg Length:

Between 0.860 inches and 0.900 inches

Second Leg Width:

Between 0.600 inches and 0.640 inches

First Leg Slot Length:

Between 0.330 inches and 0.350 inches

First Leg Slot Width:

Between 0.212 inches and 0.224 inches

Second Leg Hole Diameter:

0.281 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.300 inches and 0.320 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.300 inches and 0.320 inches

First Leg Thickness:

Between 0.045 inches and 0.055 inches

Second Leg Thickness:

Between 0.045 inches and 0.055 inches

Center Section Height:

Between 0.410 inches and 0.430 inches

Center Section Width:

Between 0.600 inches and 0.640 inches

Center Section Thickness:

Between 0.045 inches and 0.055 inches

First Leg Width:

Between 0.600 inches and 0.640 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.300 inches and 0.320 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.300 inches and 0.320 inches

First Leg End Radius:

Between 0.300 inches and 0.320 inches

Second Leg End Radius:

Between 0.300 inches and 0.320 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0