

View Online at <https://aerobasegroup.com/nsn/5340-00-802-9188>

**Fabrication Method (non-core):**

Stamped

**First Leg Length:**

0.880 inches

**Second Leg Length:**

1.250 inches

**Second Leg Width:**

1.000 inches

**First Leg Slot Length:**

0.500 inches

**First Leg Slot Width:**

0.220 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.490 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**Second Leg Slot Length:**

0.500 inches

**Second Leg Slot Width:**

0.220 inches

**First Leg Thickness:**

Between 0.059 inches and 0.065 inches

**Second Leg Thickness:**

Between 0.059 inches and 0.065 inches

**First Leg Width:**

1.000 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.490 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.310 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

One slot

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

One slot

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-250/11, t4 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 1 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.