

View Online at <https://aerobasegroup.com/nsn/5340-00-802-9188>

Fabrication Method (non-core):

Stamped

First Leg Length:

0.880 inches

Second Leg Length:

1.250 inches

Second Leg Width:

1.000 inches

First Leg Slot Length:

0.500 inches

First Leg Slot Width:

0.220 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.490 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.500 inches

Second Leg Slot Length:

0.500 inches

Second Leg Slot Width:

0.220 inches

First Leg Thickness:

Between 0.059 inches and 0.065 inches

Second Leg Thickness:

Between 0.059 inches and 0.065 inches

First Leg Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.490 inches

First Leg Distance From Edge To Hole Center Along Length:

0.310 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11, t4 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.