

View Online at <https://aerobasegroup.com/nsn/5340-00-804-5984>

First Leg Length:

Between 0.520 inches and 0.540 inches

Second Leg Length:

Between 0.520 inches and 0.540 inches

Second Leg Width:

Between 0.490 inches and 0.510 inches

First Leg Hole Diameter:

Between 0.216 inches and 0.226 inches

Second Leg Hole Diameter:

Between 0.276 inches and 0.286 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Thickness:

Between 0.056 inches and 0.062 inches

Second Leg Thickness:

Between 0.056 inches and 0.062 inches

Center Section Height:

Between 0.186 inches and 0.212 inches

Center Section Width:

Between 0.490 inches and 0.510 inches

Center Section Thickness:

Between 0.056 inches and 0.062 inches

First Leg Width:

Between 0.490 inches and 0.510 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg End Radius:

0.250 inches

Second Leg End Radius:

0.250 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

163.0 degrees

Second Leg Angle:

163.0 degrees

Material:

Steel comp 410

Material Specification:

Ams 5504 assn standard single material response

Style Designator:

Double angle

Fsc Application Data:

Engine, acft, turbojet

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0