

View Online at <https://aerobasegroup.com/nsn/5340-00-804-5984>

**First Leg Length:**

Between 0.520 inches and 0.540 inches

**Second Leg Length:**

Between 0.520 inches and 0.540 inches

**Second Leg Width:**

Between 0.490 inches and 0.510 inches

**First Leg Hole Diameter:**

Between 0.216 inches and 0.226 inches

**Second Leg Hole Diameter:**

Between 0.276 inches and 0.286 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Thickness:**

Between 0.056 inches and 0.062 inches

**Second Leg Thickness:**

Between 0.056 inches and 0.062 inches

**Center Section Height:**

Between 0.186 inches and 0.212 inches

**Center Section Width:**

Between 0.490 inches and 0.510 inches

**Center Section Thickness:**

Between 0.056 inches and 0.062 inches

**First Leg Width:**

Between 0.490 inches and 0.510 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg End Radius:**

0.250 inches

**Second Leg End Radius:**

0.250 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Identical

**First Leg Angle:**

163.0 degrees

**Second Leg Angle:**

163.0 degrees

**Material:**

Steel comp 410

**Material Specification:**

Ams 5504 assn standard single material response

**Style Designator:**

Double angle

**Fsc Application Data:**

Engine, acft, turbojet

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0