

View Online at <https://aerobasegroup.com/nsn/5340-00-808-1002>

Fabrication Method (non-core):

Machined

First Leg Length:

0.730 inches

Second Leg Length:

0.970 inches

End Application:

W/s: engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); aircraft, strato fortress b-52; engine, aircraft, tf-33-p-7 (c-141a/b); engine, aircraft tf33-p-3/5/9 (c/ec-135, b-52h)

Second Leg Width:

4.220 inches

Second Leg Corner Radius:

0.219 inches

First Leg Hole Diameter:

Between 0.339 inches and 0.349 inches

First Leg Thickness:

Between 0.028 inches and 0.034 inches

Second Leg Thickness:

Between 0.028 inches and 0.034 inches

First Leg Distance Between Lower Hole Centers Along Width:

1.919 inches

First Leg Distance Between Hole Centers Along Length:

0.031 inches

First Leg Distance Between First And Second Hole Centers Along Width:

0.959 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Corner radius

First Leg Angle:

90.0 degrees

Material:

Steel comp 4130 or steel comp 8630

Material Specification:

Ams 6350 assn standard 1st material response or ams 6355 assn standard 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0