NSN 5340-00-808-4557

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-808-4557

First Leg Length:

1.048 inches

Second Leg Length:

Between 1.048 inches and 1.058 inches

Second Leg Width:

1.792 inches

First Leg Hole Diameter:

Between 0.339 inches and 0.349 inches

Second Leg Hole Diameter:

Between 0.276 inches and 0.286 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.896 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.290 inches

First Leg Thickness:

Between 0.058 inches and 0.068 inches

Second Leg Thickness:

Between 0.058 inches and 0.068 inches

First Leg Width:

1.792 inches

First Leg Corner Radius:

0.344 inches

First Leg Distance Between Hole Centers Along Width:

1.104 inches

First Leg Distance From Edge To Hole Center Along Width:

0.344 inches

First Leg Distance From Edge To Hole Center Along Length:

0.344 inches

Second Leg End Radius:

0.375 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

NSN 5340-00-808-4557 Angle Bracket - Page 2 of 2

A042a0



| Material: |
|--|
| Steel comp 4130 or steel comp 8630 |
| Material Specification: |
| Ams 6350 assn standard 1st material response or ams 6355 assn standard 2nd material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Ams 2400 assn standard single treatment response |
| Style Designator: |
| Angle |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |