

View Online at <https://aerobasegroup.com/nsn/5340-00-814-0568>

First Leg Length:

0.880 inches

Second Leg Length:

4.000 inches

Second Leg Width:

2.840 inches

Second Leg Corner Radius:

0.380 inches

First Leg Hole Diameter:

0.193 inches

Second Leg Hole Diameter:

0.218 inches

Second Leg Distance Between Hole Centers Along Width:

2.080 inches

Second Leg Distance Between Hole Centers Along Length:

1.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.380 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.380 inches

First Leg Thickness:

0.080 inches

Second Leg Thickness:

0.080 inches

First Leg Width:

2.840 inches

First Leg Corner Radius:

0.380 inches

First Leg Distance Between Hole Centers Along Width:

2.080 inches

First Leg Distance From Edge To Hole Center Along Width:

0.380 inches

First Leg Distance From Edge To Hole Center Along Length:

0.380 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Heat Treatment:

Cold worked

Material:

Steel comp 301 and steel comp 302

Material Specification:

Mil-s-5059, 1/4 h military specification single material response

Surface Treatment:

Passivate

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0

Mil-std (military Standard):

Mil-s-5059 spec.