

View Online at <https://aerobasegroup.com/nsn/5340-00-814-3343>

Thread Class:

3a rod connection

Thread Direction:

Right-hand rod connection

Thread Length:

0.460 inches rod connection

Shank Length:

0.680 inches

Hole Diameter:

Between 0.374 inches and 0.375 inches

Shank Diameter:

0.438 inches

Overall Height:

0.800 inches

Overall Width:

Between 1.060 inches and 1.065 inches

End Radius:

0.400 inches

Metallic Hardness Rating:

34.0 rockwell c and 38.0 rockwell c

Fork Span Width:

Between 0.700 inches and 0.705 inches

Securing Pin Hole Diameter:

0.106 inches

Distance From Center Of Securing Pin Hole To Rod End:

0.148 inches

Distance From Pivot Pinhole Center To Rod Connection End:

2.140 inches

Fork Arm Thickness:

0.180 inches

Fork Depth:

0.400 inches

Shank Shoulder Diameter:

Between 0.471 inches and 0.472 inches

Shank Shoulder Length:

0.300 inches

Thread Size:

0.438 inches rod connection

Material:

Steel comp 8740

Material Specification:

Mil-s-6049 military specification single material response

Surface Treatment:

Phosphate

Style Designator:

Clevis

Thread Series Designator:

Unf rod connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A264a0

Mil-std (military Standard):

Mil-s-6049 spec.