

View Online at <https://aerobasegroup.com/nsn/5340-00-819-6129>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

1.002 inches

**Second Leg Length:**

Between 1.180 inches and 1.220 inches

**Second Leg Width:**

Between 0.615 inches and 0.635 inches

**First Leg Hole Diameter:**

Between 0.339 inches and 0.349 inches

**Second Leg Hole Diameter:**

Between 0.214 inches and 0.224 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.293 inches and 0.333 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.290 inches and 0.310 inches

**First Leg Thickness:**

Between 0.056 inches and 0.068 inches

**Second Leg Thickness:**

Between 0.056 inches and 0.068 inches

**First Leg Width:**

Between 1.132 inches and 1.192 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.842 inches and 0.882 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.293 inches and 0.333 inches

**First Leg End Radius:**

Between 0.469 inches and 0.531 inches

**Second Leg End Radius:**

Between 0.469 inches and 0.531 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 4130

**Material Specification:**

Ams 6350 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0