

View Online at <https://aerobasegroup.com/nsn/5340-00-819-6129>

Fabrication Method (non-core):

Machined

First Leg Length:

1.002 inches

Second Leg Length:

Between 1.180 inches and 1.220 inches

Second Leg Width:

Between 0.615 inches and 0.635 inches

First Leg Hole Diameter:

Between 0.339 inches and 0.349 inches

Second Leg Hole Diameter:

Between 0.214 inches and 0.224 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.293 inches and 0.333 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.290 inches and 0.310 inches

First Leg Thickness:

Between 0.056 inches and 0.068 inches

Second Leg Thickness:

Between 0.056 inches and 0.068 inches

First Leg Width:

Between 1.132 inches and 1.192 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.842 inches and 0.882 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.293 inches and 0.333 inches

First Leg End Radius:

Between 0.469 inches and 0.531 inches

Second Leg End Radius:

Between 0.469 inches and 0.531 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 4130

Material Specification:

Ams 6350 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0