

View Online at <https://aerobasegroup.com/nsn/5340-00-819-6153>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.850 inches and 0.856 inches

Second Leg Length:

Between 0.880 inches and 0.886 inches

Second Leg Width:

2.824 inches

Second Leg Corner Radius:

0.312 inches

First Leg Hole Diameter:

Between 0.214 inches and 0.224 inches

First Leg Thickness:

Between 0.056 inches and 0.062 inches

Second Leg Thickness:

Between 0.056 inches and 0.062 inches

Center Section Height:

Between 0.456 inches and 0.462 inches

Center Section Width:

2.824 inches

Center Section Thickness:

Between 0.056 inches and 0.062 inches

First Leg Width:

2.824 inches

First Leg Corner Radius:

0.312 inches

First Leg Distance Between Hole Centers Along Width:

2.200 inches

First Leg Distance From Edge To Hole Center Along Width:

0.312 inches

First Leg Distance From Edge To Hole Center Along Length:

0.312 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Material:

Steel comp 410

Material Specification:

Ams 5504 assn standard single material response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0