## NSN 5340-00-819-6832

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-819-6832

**Fabrication Method (non-core):** 

Machined

Second Leg Width:

Between 0.490 inches and 0.510 inches

First Leg Hole Diameter:

Between 0.278 inches and 0.282 inches

**Second Leg Hole Diameter:** 

Between 0.278 inches and 0.282 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg Thickness:

Between 0.070 inches and 0.080 inches

Second Leg Thickness:

Between 0.070 inches and 0.080 inches

**Center Section Height:** 

Between 0.140 inches and 0.160 inches

**Center Section Width:** 

Between 0.490 inches and 0.510 inches

**Center Section Thickness:** 

Between 0.070 inches and 0.080 inches

First Leg Width:

Between 0.490 inches and 0.510 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg End Radius:

Between 0.344 inches and 0.406 inches

Second Leg End Radius:

Between 0.344 inches and 0.406 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

**Second Leg Hole Arrangement Style:** 

One hole

Material:

Steel

## NSN 5340-00-819-6832

Double Angle Bracket - Page 2 of 2



Ams2544 assn standard single material response

**Style Designator:** 

Double angle

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A042a0