

View Online at <https://aerobasegroup.com/nsn/5340-00-819-6832>

Fabrication Method (non-core):

Machined

Second Leg Width:

Between 0.490 inches and 0.510 inches

First Leg Hole Diameter:

Between 0.278 inches and 0.282 inches

Second Leg Hole Diameter:

Between 0.278 inches and 0.282 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg Thickness:

Between 0.070 inches and 0.080 inches

Second Leg Thickness:

Between 0.070 inches and 0.080 inches

Center Section Height:

Between 0.140 inches and 0.160 inches

Center Section Width:

Between 0.490 inches and 0.510 inches

Center Section Thickness:

Between 0.070 inches and 0.080 inches

First Leg Width:

Between 0.490 inches and 0.510 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg End Radius:

Between 0.344 inches and 0.406 inches

Second Leg End Radius:

Between 0.344 inches and 0.406 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Material:

Steel

Material Specification:

Ams2544 assn standard single material response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0