

View Online at <https://aerobasegroup.com/nsn/5340-00-821-6571>

First Leg Length:

Between 0.553 inches and 0.573 inches

Second Leg Length:

Between 0.963 inches and 0.983 inches

Second Leg Width:

Between 0.600 inches and 0.640 inches

First Leg Hole Diameter:

0.219 inches

Second Leg Hole Diameter:

0.281 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.290 inches and 0.320 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.305 inches

First Leg Thickness:

Between 0.057 inches and 0.069 inches

Second Leg Thickness:

Between 0.057 inches and 0.069 inches

First Leg Width:

Between 0.600 inches and 0.640 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.290 inches and 0.320 inches

First Leg Distance From Edge To Hole Center Along Length:

0.175 inches

First Leg End Radius:

Between 0.420 inches and 0.450 inches

Second Leg End Radius:

Between 0.420 inches and 0.450 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Surface Treatment:

Silicon

Surface Treatment Specification:

F50t12b, fscm 24446 mfr ref single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0