

View Online at <https://aerobasegroup.com/nsn/5340-00-825-1745>

First Leg Length:

Between 0.859 inches and 0.891 inches

Second Leg Length:

Between 0.421 inches and 0.453 inches

Second Leg Width:

Between 0.734 inches and 0.766 inches

First Leg Hole Diameter:

Between 0.193 inches and 0.225 inches

Second Leg Hole Diameter:

Between 0.136 inches and 0.168 inches

Second Leg Distance Between Hole Centers Along Width:

Between 0.359 inches and 0.391 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.171 inches and 0.203 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.140 inches and 0.172 inches

First Leg Thickness:

Between 0.048 inches and 0.080 inches

Second Leg Thickness:

Between 0.048 inches and 0.080 inches

First Leg Width:

Between 0.486 inches and 0.516 inches

First Leg End Width:

Between 0.234 inches and 0.266 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.234 inches and 0.266 inches

First Leg Distance From Edge To Hole Center Along Length:

0.234 inches

First Leg Style:

Square and tapered

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 1009

Surface Treatment:

Zinc

Surface Treatment Specification:

Mil-p-12011, class rsc military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-p-12011 spec.