

View Online at <https://aerobasegroup.com/nsn/5340-00-825-1745>

**First Leg Length:**

Between 0.859 inches and 0.891 inches

**Second Leg Length:**

Between 0.421 inches and 0.453 inches

**Second Leg Width:**

Between 0.734 inches and 0.766 inches

**First Leg Hole Diameter:**

Between 0.193 inches and 0.225 inches

**Second Leg Hole Diameter:**

Between 0.136 inches and 0.168 inches

**Second Leg Distance Between Hole Centers Along Width:**

Between 0.359 inches and 0.391 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.171 inches and 0.203 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.140 inches and 0.172 inches

**First Leg Thickness:**

Between 0.048 inches and 0.080 inches

**Second Leg Thickness:**

Between 0.048 inches and 0.080 inches

**First Leg Width:**

Between 0.486 inches and 0.516 inches

**First Leg End Width:**

Between 0.234 inches and 0.266 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.234 inches and 0.266 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.234 inches

**First Leg Style:**

Square and tapered

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 1009

**Surface Treatment:**

Zinc

**Surface Treatment Specification:**

Mil-p-12011, class rsc military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-p-12011 spec.